# RESEARCH

# **Open Access**

# The optimization of the number of deployed antennas in large-scale CL-DAS for energy efficiency



Yonggue Han<sup>1</sup> and Dongkyu Sim<sup>2\*</sup>

\*Correspondence: dongkyu.sim@chungbuk.ac.kr

 <sup>1</sup> Samsung Electronics Co., Ltd., Suwon, South Korea
 <sup>2</sup> School of Information and Communication Engineering, Chungbuk National University, Cheongju, South Korea

# Abstract

We consider the deployment of a large-scale circular layout-distributed antenna system. To maximize energy efficiency, we define the optimization problem with the approximated analysis and find the number of deployed antennas as a closedform solution. In simulation results, we verify that the analysis based on approximation is accurate and the closed-form solution can achieve near-optimal energy efficiency without an exhaustive search method.

**Keywords:** Large-scale circular layout-distributed antenna system, Antenna deployment, Optimization, Energy efficiency

# **1** Introduction

A massive multiple-input multiple-output (MIMO) system, also known as a large-scale MIMO system, is considered a key technology to guarantee the requirements of next-generation communications [1, 2]. Especially, a centralized massive MIMO system can improve overall performances including spectral efficiency (SE) and link reliability by adopting a large number of antennas at the base station. However, the spatial correlation of co-located antennas at the base station limits the performance of a massive MIMO system. Moreover, a centralized massive MIMO system is not efficient to provide high-quality service for cell-edge users.

To handle these problems, the distributed antenna system (DAS) was introduced [3– 7]. In DAS, the antennas are geometrically separated from each other within a cell and each distributed antenna (DA) is controlled by a central unit (CU) via dedicated channels. Therefore, the average distance between DAs and users is shorter than the centralized MIMO system and DAS can achieve enhanced performance by mitigating the effects of spatial correlation and path loss. Adopting a large number of antennas has advantages in both a centralized MIMO system and DAS, especially, in view of the SE [8]. However, as the energy consumption used by the antennas rapidly increases, the energy efficiency (EE), which is defined as the total data rate divided by the overall power consumption, of the massive MIMO system decreases [9].



© The Author(s) 2023. **Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit http:// creativeCommons.org/licenses/by/4.0/.

The downlink capacity of multicell DAS is analyzed in [3] and a comprehensive overview of DAS in high-speed trains is introduced in [4]. The authors in [5] proposed an antenna selection and user clustering method to maximize the EE of large-scale DAS. In [6], the power allocation method for circular layout-DAS (CL-DAS) to maximize the EE was proposed. The authors in [7] analyzed the achievable data rate of large-scale CL-DAS and optimized the location of DAs to maximize the average data rate. Note that the existing studies mainly focused on resource allocation with numerical approaches, and large-scale DAS and EE were rarely considered at the same time. In [5], methods for maximizing the EE of large-scale DAS were presented, but they were heuristic algorithms without analysis. Moreover, even though an antenna deployment of the largescale DAS significantly affects the EE of the system, not enough study on that subject has been done yet.

In this paper, we optimize an antenna deployment of large-scale CL-DAS by finding the number of deployed antennas. Especially, the optimization problem to maximize the EE of the system is defined and we perform an analysis based on an approximation to express the EE by the system parameters, explicitly. With the explicit expression, we solve the approximated optimization problem and obtain the number of deployed antennas as a closed-form solution. Simulation results show the validity of the approximated analysis. We also demonstrate that the closed-form solution of the optimization problem can attain almost the same EE compared with the optimal EE which is obtained by an exhaustive search method.

# 2 System model

Figure 1 illustrates the architecture of a multi-user downlink large-scale CL-DAS. The system consists of one CU, *M* DAs which are perfectly controlled by CU, and  $K(\leq M)$  users with one receive antenna each. A CU coordinates the operation of DAs and



Fig. 1 A multi-user downlink large-scale CL-DAS

exchanges limited information between a CU and DAs such as configuration parameters, control parameters, and traffic load information [10]. We assume that DAs are uniformly located on the circle with a radius of r and its center is the same as that of the cell. Moreover, K users are uniformly distributed within the cell coverage radius Rand the distance from the center of the cell to the kth user is denoted as  $x_k$ . Then, the downlink channel can be expressed as

$$\mathbf{G} = \mathbf{L} \circ \mathbf{H},\tag{1}$$

where  $\mathbf{G} = \begin{bmatrix} \mathbf{g}_1^T \cdots \mathbf{g}_k^T \cdots \mathbf{g}_k^T \end{bmatrix}^T$  denotes a  $K \times M$  channel matrix whose (k, m) element  $g_{k,m}$  is a complex channel coefficient associated with the *m*th DA and the receive antenna of the *k*th user,  $\mathbf{g}_k$  is the *k*th user's channel vector of  $1 \times M$  size, **L** and **H** are a large-scale fading and a small-scale fading matrix, respectively, and "o" denotes the Hadamard product. Note that  $g_{k,m} = \beta_{k,m}h_{k,m}$  where  $\beta_{k,m}$  and  $h_{k,m}$  are the (k,m) elements of **L** and **H**. We assume that the large-scale fading factor  $\beta_{k,m}$  is mainly composed of shadow fading factor  $\zeta$  and path loss factor  $d_{k,m}^{\alpha}$  where  $\zeta$  is a random variable with log-normal distribution with standard deviation of  $\sigma_{sh}^2$ ,  $d_{k,m}$  is the distance between the *m*th DA and the *k*th user, and  $\alpha$  is a path loss exponent, respectively. Therefore,  $\beta_{k,m}$  can be modeled as  $\beta_{k,m} = \sqrt{\frac{\zeta}{d_{k,m}^{\alpha}}}$ . In the case of a small-scale fading,  $h_{k,m}$  is zero mean circularly symmetric complex Gaussian random variable [11, 12]. Defining a received signal of *k*th user as  $y_k$ , we can represent a received signal vector of *K* users,  $\mathbf{y} = [y_1 \cdots y_k \cdots y_K]^T$ , as

$$\mathbf{y} = \mathbf{GVPs} + \mathbf{n},\tag{2}$$

where  $\mathbf{V} = [\mathbf{v}_1 \cdots \mathbf{v}_k \cdots \mathbf{v}_K]$  denotes an  $M \times K$  precoding matrix,  $\mathbf{v}_k$  is the *k*th user's precoding vector of  $M \times 1$  size, **P** is a  $K \times K$  diagonal matrix for power allocation whose *k*th diagonal term is given by  $\sqrt{P_k}$ ,  $\mathbf{s} = [s_1 \cdots s_k \cdots s_K]^T$  is a transmitted signal vector,  $s_k$  is the *k*th user's transmit symbol, and  $\mathbf{n} = [n_1 \cdots n_k \cdots n_K]^T$  is a noise vector. We assume that  $E[\mathbf{ss}^H] = \mathbf{I}_K$  and  $E[\mathbf{nn}^H] = N_0\mathbf{I}_K$  where  $\mathbf{I}_K$  is the identity matrix of size *K* and  $N_0$  is the noise spectral density. Then, the total data rate of the system,  $R_{tot}$ , is given by

$$R_{tot} = \sum_{k=1}^{K} R_k = W \sum_{k=1}^{K} \log_2 \left( 1 + \frac{P_k |\mathbf{g}_k \mathbf{v}_k|^2}{\sum_{j \neq k} P_j |\mathbf{g}_k \mathbf{v}_j|^2 + W N_0} \right),$$
(3)

where  $R_k$  is the *k*th user's data rate and *W* is the system bandwidth. To define the EE, we assume that the overall power consumption of the system,  $P_{tot}$ , is given by

$$P_{tot} = \eta_{PA} P_T + M P_R + P_C + \sum_{m=1}^{M} P_{BH,m},$$
(4)

where  $\eta_{PA}$  is the inefficiency of power amplifier,  $P_T = \sum_{k=1}^{K} P_k$ ,  $P_R$  and  $P_C$  denote the power consumption of RF chains and circuits, respectively, and  $P_{BH,m}$  represents the power consumption for the *m*th backhaul link of the dedicated channels [13, 14]. Then, the EE of the system can be represented as

$$EE = \frac{R_{tot}}{P_{tot}} = \frac{W \sum_{k=1}^{K} \log_2 \left( 1 + \frac{P_k |\mathbf{g}_k \mathbf{v}_k|^2}{\sum\limits_{j \neq k} P_j |\mathbf{g}_k \mathbf{v}_j|^2 + WN_0} \right)}{\eta_{PA} P_T + MP_R + P_C + \sum_{m=1}^{M} P_{BH,m}}.$$
(5)

## 3 Optimization of the number of deployed antennas for energy efficiency

To maximize the EE, we optimize the antenna deployment of large-scale CL-DAS. Considering that DAs are uniformly located on the circle, the optimization of the antenna deployment is equivalent to finding the number of DAs. Therefore, the optimization problem can be defined as

$$M^* = \arg \max_M \text{EE},\tag{6}$$

where  $M^*$  denotes the optimal number of deployed antennas. However, taking into account that  $R_{tot}$  corresponding to the numerator of the EE is not an explicit function of M, we cannot solve the optimization problem in (6), directly. Furthermore, the Hadamard product of **G** makes it hard to find the closed-form solution. Therefore, we will solve the optimization problem with approximation.

## 3.1 Approximated optimization problem

As already explained, we cannot easily analyze the channel matrix **G** of large-scale CL-DAS because it is defined by the Hadamard product. To handle this problem, we approximate  $\mathbf{G} = \mathbf{L} \circ \mathbf{H}$  as  $\mathbf{\bar{G}} = \mathbf{\bar{L}}\mathbf{H}$  which is based on matrix multiplication. With sufficiently large *M*, we can assume that an approximated large-scale fading matrix  $\mathbf{\bar{L}}$  is a diagonal matrix and it can be expressed as [12]

$$\bar{L} = \begin{bmatrix} \beta_{1,avg} & 0 & \cdots & 0 \\ 0 & \beta_{2,avg} & 0 & \vdots \\ \vdots & 0 & \ddots & 0 \\ 0 & \cdots & 0 & \beta_{K,avg} \end{bmatrix},$$
(7)

where

$$\beta_{k,avg} = \lim_{M \to \infty} \sum_{m=1}^{M} \frac{\beta_{k,m}}{M} \\ = \left(r^2 + x_k^2\right)^{-\alpha/4} {}_2F_1\left(\frac{\alpha}{8}, \frac{4+\alpha}{8}; 1; \frac{4r^2 x_k^2}{\left(r^2 + x_k^2\right)^2}\right),$$
(8)

*r* is the radius of large-scale CL-DAS,  $x_k$  is the distance from the center of the cell to the *k*th user, and  $\alpha$  is a path loss exponent. Note that  ${}_2F_1(\cdot, \cdot; \cdot; \cdot)$  in (8) is the Euler type of the hypergeometric function and defined as [15]

$${}_{2}F_{1}(a,b;c;z) = \frac{1}{B(b,c-b)} \int_{0}^{1} t^{b-1} (1-t)^{c-b-1} (1-zt)^{-a} dt,$$
<sup>(9)</sup>

where  $B(\cdot, \cdot)$  indicates the beta function. Therefore, assuming  $\bar{G} = \bar{L}H$ , we can approximate  $R_{tot}$  as

$$\tilde{R}_{tot} = W \sum_{k=1}^{K} \log_2 \left( 1 + \frac{\beta_{k,avg}^2 P_k |\mathbf{h}_k \mathbf{v}_k|^2}{\sum_{j \neq k} \beta_{k,avg}^2 P_j |\mathbf{h}_k \mathbf{v}_j|^2 + W N_0} \right),$$
(10)

where  $\mathbf{h}_k$  is the *k*th row vector of **H**. Compared with (3),  $\tilde{R}_{tot}$  is easy to analyze because  $\mathbf{g}_k$  based on the Hadamard product is replaced by  $\mathbf{h}_k$ . Utilizing the statistical characteristics of  $\mathbf{h}_k$ , we can express (10) in terms of *M* according to the type of precoder and power allocation.

From now on, to focus on the effect of the antenna deployment, we assume a zeroforcing beamforming (ZFBF) with equal power allocation. Therefore, the precoding matrix **V** is given by  $\mathbf{V} = \mathbf{H}^H (\mathbf{H}\mathbf{H}^H)^{-1} \mathbf{D}$  and  $P_k = P_T/K$ . Note that the power normalization matrix **D** is a diagonal matrix whose *k*th diagonal element  $D_k = \frac{1}{\sqrt{\left[(\mathbf{H}\mathbf{H}^H)^{-1}\right]_{k,k}}}$ 

[16]. Since ZFBF eliminates inter-user interference, we only need to calculate the average desired channel gain of ZFBF,  $E\left[|\mathbf{h}_k \mathbf{v}_k|^2\right]$ , in (10). Considering that  $|\mathbf{h}_k \mathbf{v}_k|^2 = D_k^2$  is a Chi-square random variable whose distribution is defined by  $f(x) = \frac{e^{-x}x^{M-K}}{(M-K)!}$  [17], by applying the integration by parts, the average desired channel gain of ZFBF,  $E\left[|\mathbf{h}_k \mathbf{v}_k|^2\right]$ , can be calculated as

$$E\left[|\mathbf{h}_{k}\mathbf{v}_{k}|^{2}\right] = E\left[D_{k}^{2}\right] = \int_{0}^{\infty} x \cdot \frac{e^{-x}x^{M-K}}{(M-K)!}dx$$
  
$$= \frac{1}{(M-K)!} \int_{0}^{\infty} e^{-x} \cdot x^{M-K+1}dx$$
  
$$= \frac{(M-K+1)!}{(M-K)!} \int_{0}^{\infty} e^{-x}dx = M-K+1.$$
 (11)

Therefore, we can rewrite  $\tilde{R}_{tot}$  as

$$\tilde{R}_{tot} = W \sum_{k=1}^{K} \log_2 \left( 1 + \beta_{k,avg}^2 \frac{P_T}{K} \frac{M - K + 1}{W N_0} \right).$$
(12)

Finally, approximating  $\beta_{k,avg}^2 \approx \beta_{avg}^2 = \left(\sum_{k=1}^K \beta_{k,avg}^2\right)/K$ , we can obtain an approximated optimization problem with explicit expression of *M* as

$$M^* = \arg \max_{M} EE^{approx},$$
(13)

where

$$EE^{approx} = \frac{\tilde{R}_{tot}}{P_{tot}} = \frac{WK \log_2 \left(1 + \beta_{avg}^2 \frac{P_T}{K} \frac{M - K + 1}{W N_0}\right)}{\eta_{PA} P_T + M P_R + P_C + \sum_{m=1}^M P_{BH,m}}.$$
(14)

## 3.2 Closed-form solution

In this subsection, we prove that the objective function,  $EE^{approx}$ , of (13) is concave to M and find the solution as a closed-form by using the Lambert-W function.

First, we define  $EE^{approx}$  as a function *L* of *M*:

$$\mathcal{L}(M) = \frac{WK \log_2 \left( 1 + \beta_{avg}^2 \frac{P_T}{K} \frac{M - K + 1}{W N_0} \right)}{\eta_{PA} P_T + M P_R + P_C + \sum_{m=1}^M P_{BH,m}}.$$
(15)

Because the numerator of *L* is a logarithmic function to *M* and the denominator of *L* is a linear function to *M*, (15) is concave to *M*. Since the function *L* of *M* is concave, we can find a unique global optimal point  $M^*$  of an approximated optimization problem by solving the following equation:

$$\left. \frac{\partial L}{\partial M} \right|_{M=M^*} = 0. \tag{16}$$

Calculating (16), we can obtain the closed-form solution for the number of deployed antenna  $M^*$  as

$$M^* = (\kappa - 1) \left( \frac{W N_0 K}{\beta_{avg}^2 P_T} \right) + K - 1, \tag{17}$$

where 
$$\kappa = e^{\lambda + 1}$$
,  $\lambda = W\left(\frac{\mu}{e}\right)$  and  $\mu = \frac{\beta_{avg}^2}{WN_0} \frac{P_T}{K} \left(\frac{\eta_{PA}P_T + P_C + \sum\limits_{m=1}^{M} P_{BH,m}}{P_R} + K - 1\right) - 1$ . Here,

*W* denotes the Lambert-W function, which is defined as  $W(z)e^{W(z)} = z$  where *z* is any complex number [18]. Considering that the closed-form solution (17) is explicitly expressed by *K*, *W*, *P*<sub>T</sub>, *P*<sub>R</sub>, *P*<sub>C</sub>, *P*<sub>BH,m</sub> and other system parameters, we can easily analyze the effect of each system parameter on the number of deployed antennas. Moreover, by substituting (17) into (14), we can obtain the closed-form expression of EE. Note that since the closed-form solution is optimal for an approximated optimization problem, it cannot guarantee the optimality of the antenna deployment. Therefore, we will verify the accuracy of the closed-form solution in the simulation section.

## 4 Simulation results and discussion

From the simulation results, we verify the validity of the approximation for the analysis and accuracy of the closed-form solution. *K* users are uniformly distributed within the cell coverage and there is the minimum separation distance between a user and a DA, guard distance. Other system parameters used in the simulations are described in Table 1. Note that all the simulation results are obtained by averaging over multiple snapshots.

Figure 2 shows true EE value and approximated EE value based on (5) and (14), respectively, according to the number of deployed antennas, M. We performed simulations for various K, from 5 to 40, and the optimization of the number of deployed antennas is not applied. Comparing true EE value and approximated EE value in the

Parameter	Notation	Value
Transmit power	PT	35 [dBm]
Noise spectral density	No	-104 [dBm]
Cell radius	R	1000 [m]
Shadow fading standard deviation	$\sigma_{sh}$	4 [dB]
Path loss exponent	α	2
System bandwidth	W	10 [MHz]
Antenna gain	$\phi_{\scriptscriptstyle C}$	1
Guard distance	$\mathcal{G}_d$	20 [m]
DAs' radius	r	2R/3
Power inefficiency of power amplifier	$\eta_{PA}$	1/0.12
Circuit power consumption	$P_C$	45 [W]
RF chain power consumption	$P_R$	4.5 [W]
mth backhaul link power consumption	P <sub>BH,m</sub>	1.075 [W]



Fig. 2 True and approximated EE value according to various *M* and *K* 

simulations, we can verify that the analysis based on approximation is valid even though the number of deployed antennas is finite. Moreover, we can confirm that (15), a function L of M, is concave as we explained, regardless of the number of users K.

Figure 3 represents the number of deployed antennas over the various number of users and it was obtained by the closed-form solution (17) and an exhaustive search method. For the simulation results of an exhaustive search method, we calculated EE for all possible candidates and chose the optimal number of deployed antennas maximizing EE for every channel realization. Compared to an exhaustive search method, the number of deployed antennas based on the analysis differs by a maximum of three, which is only about a 5% difference. This gap between the exhaustive search



Fig. 3 The number of deployed antennas by the closed-form solution and an exhaustive search method

method and closed-form solution comes from the large-scale fading approximation and conversion process of a closed-form solution (17) to an integer. However, considering the high computational complexity of an exhaustive search method, we can conclude that the closed-form solution based on approximation is very effective for the real-time operations of practical systems.

Figure 4 describes the optimal EE by an exhaustive search method and achievable EE by the closed-form solution over the various number of users, *K*. As shown in Fig. 4,



Fig. 4 Optimal EE by an exhaustive search method and achievable EE by the closed-form solution

utilizing the closed-form solution based on the analysis with approximation, we can achieve nearly optimal EE without an exhaustive search method.

## **5** Conclusion

In this paper, we approximated the function of EE in the large-scale CL-DAS and optimized an antenna deployment to maximize the EE. Especially, by solving the optimization problem, we found the number of deployed antennas as a closed-form solution. Simulation results showed that the analysis based on approximation is valid and nearly optimal EE can be achieved in a closed-form solution compared with an exhaustive search method. However, since the CL-DAS is not general architecture, the results of this study have a limitation. Therefore, in future works, we will extend the research to a generalized system model, large-scale random layout-DAS.

## 6 Methods/experimental

The purpose of this study is to optimize an antenna deployment of the large-scale CL-DAS in view of EE. The large-scale CL-DAS consists of one CU, M DAs, and K users with one receive antenna each. DAs are uniformly located on the circle with a radius of r and users are uniformly distributed within the cell coverage radius R. The channels between DAs and users are modeled based on Hadamard product of large-scale fading and small-scale fading. For given system parameters including the number of DAs and users, the energy efficiency can be calculated by utilizing the solution of an approximated optimization problem.

#### Abbreviations

MIMO	Multiple-input multiple-output
SE	Spectral efficiency
DAS	Distributed antenna system
DA	Distributed antenna
CU	Central unit
EE	Energy efficiency
CL-DAS	Circular layout-distributed antenna system
RF	Radio frequency
ZFBF	Zero-forcing beamforming

## Acknowledgements

This research was supported by Basic Science Research Program through the National Research Foundation of Korea (NRF) funded by the Ministry of Education (No. 2020R1A6A1A12047945).

#### Author contributions

Han presented the basic idea, developed the theory, and performed the simulations. Sim verified the analytical methods and wrote the manuscript. All authors discussed the results and approved the final manuscript.

## Funding

This research was supported by Basic Science Research Program through the National Research Foundation of Korea (NRF) funded by the Ministry of Education (No. 2020R1A6A1A12047945).

## Availability of data and materials

My manuscript has no associated data and materials.

## Declarations

## Competing interests

The authors declare that they have no competing interests.

Received: 13 December 2022 Accepted: 15 September 2023 Published online: 25 September 2023

## References

- L. Lu, G.Y. Li, A.L. Swindlehurst, A. Ashikhmin, R. Zhang, An overview of massive mimo: benefits and challenges. IEEE J. Sel. Topics Signal Process. 8(5), 742–758 (2014)
- M. Matthaiou, O. Yurduseven, H.Q. Ngo, D. Morales-Jimenez, S.L. Cotton, V.F. Fusco, The road to 6g: ten physical layer challenges for communications engineers. IEEE Commun. Mag. 59(1), 64–69 (2021)
- 3. W. Choi, J.G. Andrews, Downlink performance and capacity of distributed antenna systems in a multicell environment. IEEE Trans. Wirel. Commun. 6(1), 69–73 (2007)
- J. Wang, H. Zhu, N.J. Gomes, Distributed antenna systems for mobile communications in high speed trains. IEEE J. Sel. Areas Commun. 30(4), 675–683 (2012)
- J. Joung, Y.K. Chia, S. Sun, Energy-efficient, large-scale distributed-antenna system (I-das) for multiple users. IEEE J. Sel. Topics Signal Process. 8(5), 954–965 (2014)
- H. Kim, S.-R. Lee, C. Song, K.-J. Lee, I. Lee, Optimal power allocation scheme for energy efficiency maximization in distributed antenna systems. IEEE Trans. Commun. 63(2), 431–440 (2015)
- A. Yang, Y. Jing, C. Xing, Z. Fei, J. Kuang, Performance analysis and location optimization for massive mimo systems with circularly distributed antennas. IEEE Trans. Wirel. Commun. 14(10), 5659–5671 (2015)
- G.N. Kamga, M. Xia, S. Aïssa, Spectral-efficiency analysis of massive mimo systems in centralized and distributed schemes. IEEE Trans. Commun. 64(5), 1930–1941 (2016)
- H.Q. Ngo, E.G. Larsson, T.L. Marzetta, Energy and spectral efficiency of very large multiuser mimo systems. IEEE Trans. Commun. 61(4), 1436–1449 (2013)
- H.Q. Ngo, A. Ashikhmin, H. Yang, E.G. Larsson, T.L. Marzetta, Cell-free massive mimo versus small cells. IEEE Trans. Wirel. Commun. 16(3), 1834–1850 (2017)
- B. Sklar, Rayleigh fading channels in mobile digital communication systems. i. characterization. IEEE Commun. Mag. 35(7), 90–100 (1997)
- Y. Han, J. Lee, D. Sim, C. Lee, Asymptotic analysis of sum rate of cl-das based on expected large scale fading. IEEE Wirel. Commun. Lett. 8(1), 121–124 (2019)
- O. Arnold, F. Richter, G. Fettweis, O. Blume, Power consumption modeling of different base station types in heterogeneous cellular networks, in *Proceedings of the 2010 Future Network & Mobile Summit*, pp. 1–8 (2010)
- H.Q. Ngo, L.-N. Tran, T.Q. Duong, M. Matthaiou, E.G. Larsson, On the total energy efficiency of cell-free massive mimo. IEEE Trans. Green Commun. Netw. 2(1), 25–39 (2018)
- M. Abramowitz, I.A. Stegun, Handbook of Mathematical Functions With Formulas, Graphs, and Mathematical Tables (Dover, New York, 1972)
- T. Yoo, A. Goldsmith, On the optimality of multiantenna broadcast scheduling using zero-forcing beamforming. IEEE J. Select. Areas Commun. 24(3), 528–541 (2006)
- D.A. Gore, R.W. Heath, A.J. Paulraj, Transmit selection in spatial multiplexing systems. IEEE Commun. Lett. 6(11), 491–493 (2002)
- R.M. Corless, G.H. Gonnet, D.E.G. Hare, D.J. Jeffrey, D.E. Knuth, On the lambert w function. Adv. Comput. Math. 5, 329–359 (2006)

## Publisher's Note

Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

# Submit your manuscript to a SpringerOpen<sup>®</sup> journal and benefit from:

- Convenient online submission
- Rigorous peer review
- Open access: articles freely available online
- High visibility within the field
- Retaining the copyright to your article

Submit your next manuscript at > springeropen.com